

Product information

Motorbike Fork Oil 10W medium

PI 23/27/08/2020



Description

Full synthetic fork oil and shock-absorber oil. Has been developed for universal use. Special synthetic base oils and corresponding additives guarantee optimum driveability and damping. Prevents foam formation and seal hardening. Good corrosion and wear protection provide long service life.

Properties

- prevents seals from swelling
- prevents foam formation
- good corrosion protection
- high wear resistance
- better drivability

Technical data

| | |
|---------------------|---|
| Density at 15 °C | 0,830 g/cm ³ ASTM D 7042-04 |
| Viscosity at 40 °C | 28,5 mm ² /s DIN 51757 |
| Viscosity at 100 °C | 5,7 mm ² /s ASTM D 7042-04 |
| Viscosity index | 146 DIN ISO 2909 |
| Pour point | -42 °C DIN ISO 3016 |
| Flash point | 244 °C DIN ISO 2592 |
| Color number (ASTM) | L 0,5 DIN ISO 2049 |

Areas of application

Universal use in telescopic forks and shock absorbers on motorbikes, mopeds, autocycles and other two-wheeled vehicles.

Application

Follow the instructions of the telescopic fork, shock absorber and two-wheeled vehicle manufacturers.



Available pack sizes

| | |
|-----------------------|------------------------|
| 500 ml Can plastic | 1506 D-GB-I-E-P |
| 500 ml Can plastic | 5952 D-F-I-GR |
| 1 l Can plastic | 2715 D-GB-I-E-P |
| 1 l Can plastic | 20748 GB-DK-FIN-N-S |
| 5 l Canister plastic | 1606 D-GB-I-E-P |
| 5 l Canister plastic | 5953 D-F-I-GR |
| 20 l Canister plastic | 3828 D-GB |

Our information is based on thorough research and may be considered reliable, although not legally binding.