

Motorbike Foam Filter Oil (Spray)

Description

Specially developed aerosol for wetting foam and fabric air filters. Dust and dirt are reliably deterred even under extreme operating conditions and engine damage is thus avoided. Guarantees an optimum air flow and thereby maximum engine performance.

Properties

- waterproof
- binds dust and sand
- improves filter properties
- long engine service life
- reduces wear
- extremely adherent

Technical data

Base	Polymere / polymers
Form	flüssig, aerosol / liquid, aerosol
Odor	charakteristisch / characteristic
Flash point	-60 °C
Color / appearance	blau / blue

Areas of application

Suitable for use on all two-stroke and four-stroke motorbikes with air or water-cooled engines using foam or fabric air filters.

Application

First free the filter of coarse contaminants by knocking them out. Clean air filter with Liqui Moly Motorbike Foam Filter Cleaner (part no. 1299) and moisten with Motorbike Air Filter Oil (Spray) after the solvents have evaporated. Before installing the air filter, allow it to air out for 10 to 15 minutes.

When working with Motorbike Foam Filter Oil (Spray), make sure that the area is well ventilated.



Available pack sizes

400 ml Can aerosol	1604 D-GB-I-E-P
400 ml Can aerosol	5933 D-F-I-GR
400 ml Can aerosol	20745 GB-DK-FIN-N-S

Our information is based on thorough research and may be considered reliable, although not legally binding.