LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr

Postfach 2829 89018 Ulm Germany

Product information Motorbike 4T 5W-40 HC Street

Description

High-performance motor oil based on synthetic technology. Ensures maximum performance and protection of the engine under all operating conditions. Optimum lubrication, outstanding engine cleanliness, excellent friction and minimum wear are just as much taken for granted as gentle clutch engagement and disengagement and gear shifting. Tested on engines with catalytic converters.

Properties

- guarantees low oil consumption
- high shear stability
- high wear resistance
- optimum stability to aging
- optimum lubrication under all operating conditions
- outstanding engine cleanliness
- tested for the use with catalytic converters
- especially suitable for wet clutches

Specifications and approvals:

API SN PLUS • JASO MA2

Technical data

l echnical uala	
Viscosity SAE class	5W-40 SAE J300
Density at 15 °C	0,850 g/cm³ DIN 51757
Viscosity at 40 °C	85,0 mm²/s ASTM D 7042-04
Viscosity at 100 °C	14,3 mm²/s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -30°C (CCS)	<= 6600 mPas ASTM D 5293
Viscosity index	175 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D 5481
Pour point	-36 mPas DIN ISO 2909
Evaporation loss (Noack)	11,0 % ASTM D 5800 B
Flash point	228 °C DIN ISO 2592
Total base number	7,0 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575



Technical data

Color number (ASTM)

L 2,0 DIN ISO 2049

Areas of application

Developed for air and water-cooled 4-stroke engines exposed to normal to extreme operating conditions. For sporting applications. Suitable for engines with or without a wet clutch.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. **Note:** Optimum effectiveness is only possible when the product is used unmixed.

Available pack sizes

1 l Canister plastic	20750 BOOKLET
4 l Canister plastic	20751 BOOKLET
20 l Canister plastic	21226 D-GB
60 l Drum sheet metal	20752 D-GB
205 l Drum sheet metal	21122 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.



