# **Product information**

## Motorbike 4T 15W-50 Street



## **Description**

High-performance motor oil based on synthetic technology. Ensures maximum performance and protection of the engine under all operating conditions. Optimum lubrication, outstanding engine cleanliness, excellent friction and minimum wear are just as much taken for granted as gentle clutch engagement and disengagement and gear shifting. Tested on engines with catalytic converters.

## **Properties**

- optimum stability to aging
- guarantees low oil consumption
- especially suitable for wet clutches
- tested for the use with catalytic converters
- outstanding engine cleanliness
- optimum lubrication under all operating conditions
- high wear resistance
- high shear stability

## Specifications and approvals:

API SN PLUS • JASO MA2

#### **Technical data**

SAE class (engine oils) 15W-50 SAE J 300 Density at 15 °C 0,870 g/cm³ DIN 51757

Viscosity at 40 °C 140,0 mm²/s ASTM D 7042-04

Viscosity at 100 °C 18,3 mm<sup>2</sup>/s

ASTM D 7042-04

Viscosity at -25°C (MRV) < 60000 mPas

ASTM D4684

Viscosity at -20°C (CCS) <= 7000 mPas

**ASTM D5293** 

Viscosity index 145

**DIN ISO 2909** 

HTHS at  $150^{\circ}$ C >= 3,7 mPas

ASTM D5481

Pour point -30 °C

**DIN ISO 3016** 

Evaporation loss (Noack) 10,6 %

CEC-L-40-A-93

Flash point 230 °C

**DIN ISO 2592** 

Total base number 7,0 mg KOH/g

DIN ISO 3771

Sulfate ash 0,8 g/100g

DIN 51575



#### **Technical data**

Color number (ASTM) L 2,5

**DIN ISO 2049** 

### Areas of application

Developed for air and water-cooled 4-stroke engines exposed to normal to extreme operating conditions. For sporting applications. Suitable for engines with or without a wet clutch.

### **Application**

The operating instructions of the engine manufacturers must be followed.

Note: Optimum effectiveness only when the product is used on its own (i.e. no mixing).

#### Available pack sizes

Available pack Sizes	
1 l Canister plastic	2555 BOOKLET
1 l Canister plastic	1756 JP
4 l Canister plastic	1689 BOOKLET
20 l Canister plastic	2722 D-GB-I-E-P
60 l Drum sheet metal	2565 D-GB
205 l Drum sheet metal	2566 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.