Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de

# Description

Preserves and protects fuel against aging and oxidation. Prevents corrosion throughout the entire fuel system. Prevents problems from occurring when motorbikes, motor scooters, ATVs, snowmobiles and other gasoline-driven 2-stroke and 4-stroke engines are decommissioned. Increases operational reliability. The product has a lasting effect.

Motorbike Gasoline Stabilizer

## **Properties**

- has a lasting effect
- increases operational reliability
- simple to use
- tested for the use with catalytic converters

**Product information** 

- cost-effective due to exact dosage
- protects fuel against oxidation and aging

## **Technical data**

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in carrier liquid
Color / appearance	blau / blue
Odor	charakteristisch / characteristic
Form	flüssig / liquid
Density at 15 °C	0,822 g/cm³
Hazard class as per Ger- man VbF	A III
Flash point	>61 °C
Viscosity at 40 °C	<7 mm²/s

### Areas of application

Suitable for all 4-stroke and 2-stroke gasoline engines - especially for preventive care. Tested for turbochargers and catalytic converters.

### **Application**

Filling the dosage chamber (25 ml) once is sufficient for 5 liters of fuel. Add to the fuel and repeat dosage after refueling. Also suitable for long-term use in seldom used engines. When decommissioning, add to the fuel and let the engine run approx. 10 minutes.

Our information is based on thorough research and may be considered reliable, although not legally binding.

3041

5921

D-GB-E-P

D-F-I-GR

Available pack sizes

plastic

plastic

250 ml Dispensing bottle

250 ml Dispensing bottle





