

# Product information

## Motorbike Foam Filter Oil

PI 39/02/09/2021



### Description

Special oil for wetting foam air filters. Dust and dirt are reliably trapped even under extreme operating conditions and engine damage is thus avoided. Ensures an optimal air flow and thus maximum engine performance.

### Properties

- long engine service life
- high wear resistance
- excellent adhesion
- waterproof
- improves filter properties
- binds dust and sand

### Technical data

Density	0,798 g/cm <sup>3</sup>
Form	flüssig / liquid
Odor	charakteristisch / characteristic
Flash point	-9 °C
Color / appearance	blau / blue

### Areas of application

Suitable for use on all two-stroke and four-stroke motorbikes with air or water-cooled engines using foam air filters.

### Application

Pour Motorbike Air Filter Oil into a suitable container. Remove coarse contaminants from the foam air filter by knocking it out. After this, place foam air filter in the container filled with the product and thoroughly massage the air filter several times. Before installing the filter, allow it to dry out for 10 to 15 minutes.

**When working with Motorbike Air Filter Oil, make sure that the area is well ventilated.**



### Available pack sizes

500 ml Can sheet metal	1625
	D-GB-I-E-P
500 ml Can sheet metal	5931
	D-F-I-GR
1 l Can sheet metal	3096
	D-GB-I-E-P
1 l Can sheet metal	5932
	D-F-I-GR

**Our information is based on thorough research and may be considered reliable, although not legally binding.**